

广州市雄星塑料制品有限公司

GUANGZHOU XIONGXING PLASTIC PRODUCTS CO., LTD

12th Zone of Baisha village, LiangTian Town, Baiyun District,

Guangzhou, China

TEL:0086-20-87480381

VALMATEX POLYCRYSTAL® NF 0543

Super clear PVC film

Features:

- Water resistance
- High strength material
- UV resistance
- No yellowing

Description:

Width: 1.4; 1.8; 2.0 m.

Length: 50 m

Serviceable life: Up to 1 year

General application: Production of curtains at cleaning stations.

Technical features:

Test item	Test method	Value
Thickness	USE SM-112 Side gauges to test thickness	0,5 mm
PHR (degree of softness)	--	43
Total Weight	Use DH-300 Direct-reading electronic tool measure it	650±20 gr/m2
Cold resistance	Use GDW-80C high and low Test chamber test it	-15 °C
Heat resistance	Use KH-35A Electric heating constant temperature drying oven test it	180 °C
Dimensional Stability at 60°C	Use KH-35A Electric heating constant temperature drying oven test it	MD < 3 % CD < 2 %
Tensile strength	Use computer Tensile testing machine measure it	CD : 21.63 MPA MD : 25.9 MPA
Tear strength	Use computer Tensile testing machine measure it	CD: 251.6 % MD: 224.4 %

UV resistant	Using xenon lamp/ XL - 1000 UV complex climate resistance tester measure it	6 months
Non-yellowing	Using xenon lamp/ XL - 1000 UV complex climate resistance tester measure it	Yes
Single-layer	--	Yes
Waterproof	Digital water bath thermostat oscillator for water resistance	Waterproof, but can't always soaked in water and not move

Supplied in rolls on cores, packaged in a hard cardboard tube.

Remarks:

It is hereby certified, that the material above has been inspected and tested in accordance with the conditions and requirements of the contract of Purchase order and, unless agreed otherwise, confirms in all respects to the specification relevant thereto.

GUANGZHOU XIONGXING PLASTIC PRODUCTS CO.,LTD.

广州市雄星塑料制品有限公司

GUANGZHOU CHINA

中国 广州